



45369 ROUND REGRESSED GIMBAL



The Midway collection is a family of integrated led recessed lights available in sizes ranging from 2"-6". With their durable die cast aluminum bodies and built on CCT color selecting switch Midway family fixtures are aesthetically appealing, functional and extremely versatile. Their IC rated shallow bodies allow them to be used in most residential and commercial installations with or without insulation in the ceiling. Midway fixtures are available in white or black finish and come standard with a reliable phase dimming power supply.

| TYPE: | | |
|--------|--|--|
| DATE: | | |
| NOTES: | | |



2700K . 3000K . 3500K . 4000K . 5000K

SPECIFICATIONS

LIGHT HOUSING

- IC Airtight Cast aluminum body.
- Remodel application. C/W spring loaded clips.
- Mates to driver box with quick connector.
- Max Ceiling thickness 5/8".
- Approved for damp location.

DIMENSIONS

- Cut hole: ø3 3/4".
- Fixture: ø4 3/8" x 3 1/4"H.

ELECTRICAL

- 120 V Input class 2 constant current dimmable driver enclosed in junction box.
- TRIAC and ELV dimming.
- Min operating temperature (-4°F~104°F)(-20°C~-40°C).

LIGHT MODULE

- 1 x 12W Integrated LED COB.
- Lumen maintenance 70% 50,000 hrs.
- CRI: 90+
- · Beam angle: 38 degree.
- |30K |35K • Kelvin: 27K 40K |50K
- Lumen: 719 lm | 763 lm | 826 lm | 861 lm | 851 lm

CERTIFICATIONS













ORDERING GUIDE

| MODEL | FINISH |
|-----------|--------|
| 45369-025 | Black |
| 45369-018 | White |

BEAM WATTS LUMENS KELVIN DIMMABLE CRI **ADJUSTABLE** ANGLE TRIAC/ELV 38° 30° ø3 3/4" 12W Up to 861 **CCT Selectable** 90+










PRODUCT DIMENSIONS



ACCESSORIES



45611-018 60" 2 pin Connector



45372-018 **NEW CONSTRUCTION PLATE** Mounting kit includes bars 14" x 7 3/4" ø3 3/4"



45517-013 **NEW CONSTRUCTION SMASH PLATE** 13 1/4" x 6 1/2" ø3 3/4"



NO IC BOX REQUIRED